





1. Unique identification code of the product-type:	CU-LT
2. Intended use/es:	Rectangular fire damper to be used in conjunction with partitions to maintain fire compartments in heating, ventilating and air conditioning installations.
3. Manufacturer:	Rf-Technologies NV, Lange Ambachtstraat 40, B-9860 Oosterzele
4. System/s of AVCP:	System 1
5. Harmonised standard / European Assessment Document; notified body / European Technical Assessment, Technical Assessment Body, notified body; certificate of constancy of performance:	EN 15650:2010, BCCA with identification number 0749; BCCA-0749-CPR-BC1-606-0464-15650.05-0464; BCCA-0749-CPR-BC1-606-0464-15650.15-2517
6. Declared performance according to EN 15650:2010	(Fire resistance according to EN 1366-2 and classifications according to EN 13501-3)

Essential characteristics					Performance
Range	Wall type	Wall	Sealing	Installation	Classification
200x100 mm ≤ CU-LT ≤ 800x600 mm	Rigid wall	Aerated concrete ≥ 100 mm	Mortar	1	EI 90 (v <sub>e</sub> i ↔ o) S - (500 Pa)
			Gypsum	1	EI 120 (v <sub>e</sub> i ↔ o) S - (500 Pa)
			Stone wool + coating ≥ 140 kg/m <sup>3</sup> + coated casing	1	EI 120 (v <sub>e</sub> i ↔ o) S - (300 Pa)
			Stone wool + coating ≥ 140 kg/m <sup>3</sup>	1	EI 90 (v <sub>e</sub> i ↔ o) S - (300 Pa)
			Galvanised duct + stone wool + coating ≥ 150 kg/m <sup>3</sup> 1x60 mm + IFW installation kit	2	EI 60 (v <sub>e</sub> i ↔ o) S - (300 Pa)
			Galvanised duct + stone wool + coating ≥ 140 kg/m <sup>3</sup> 1x80 mm + IFW installation kit	2	EI 90 (v <sub>e</sub> i ↔ o) S - (300 Pa)
			Galvanised duct + stone wool + coating ≥ 140 kg/m <sup>3</sup> 2x50 mm + IFW installation kit	2	EI 90 (v <sub>e</sub> i ↔ o) S - (300 Pa)
			Galvanised duct + GEOFLAM® F 45 mm + mortar	2	EI 120 (v <sub>e</sub> i ↔ o) S - (500 Pa)
			Galvanised duct + GEOFLAM® Light 35 mm + mortar	2	EI 120 (v <sub>e</sub> i ↔ o) S - (500 Pa)
			Flexible wall	Metal studs gypsum plasterboard Type A (EN 520) ≥ 100 mm	IFW installation kit
	Gypsum	1			EI 60 (v <sub>e</sub> i ↔ o) S - (500 Pa)
	Stone wool + coating ≥ 140 kg/m <sup>3</sup>	1			EI 60 (v <sub>e</sub> i ↔ o) S - (300 Pa)
	Galvanised duct + stone wool + coating ≥ 150 kg/m <sup>3</sup> 1x60 mm + IFW installation kit	2			EI 60 (v <sub>e</sub> i ↔ o) S - (300 Pa)
	Metal studs gypsum plasterboard Type F (EN 520) ≥ 100 mm	IFW installation kit			3
		Gypsum		1	EI 90 (v <sub>e</sub> i ↔ o) S - (500 Pa)
		Stone wool + coating ≥ 140 kg/m <sup>3</sup> + coated casing		1	EI 120 (v <sub>e</sub> i ↔ o) S - (300 Pa)
		Stone wool + coating ≥ 140 kg/m <sup>3</sup>		1	EI 90 (v <sub>e</sub> i ↔ o) S - (300 Pa)
		Galvanised duct + stone wool + coating ≥ 140 kg/m <sup>3</sup> 2x50 mm + IFW installation kit		2	EI 90 (v <sub>e</sub> i ↔ o) S - (300 Pa)
	Rigid floor	Reinforced concrete ≥ 110 mm		Mortar	1
			Gypsum	1	EI 120 (h <sub>o</sub> i ↔ o) S - (500 Pa)
Gypsum			1	EI 120 (h <sub>o</sub> i ↔ o) S - (500 Pa)	
Reinforced concrete ≥ 150 mm		Stone wool + coating ≥ 140 kg/m <sup>3</sup> + coated casing	1	EI 120 (h <sub>o</sub> i ↔ o) S - (300 Pa)	
		Stone wool + coating ≥ 140 kg/m <sup>3</sup>	1	EI 90 (h <sub>o</sub> i ↔ o) S - (300 Pa)	
		Galvanised duct + stone wool + coating ≥ 140 kg/m <sup>3</sup> 2x50 mm + IFW installation kit	2	EI 90 (h <sub>o</sub> i ↔ o) S - (300 Pa)	
200x100 mm ≤ CU-LT + GDA ≤ 800x600 mm	Flexible wall	Metal studs gypsum plasterboard Type F (EN 520) ≥ 100 mm	GDA + stone wool ≥ 40 kg/m <sup>3</sup>	4	EI 120 (v <sub>e</sub> i ↔ o) S - (300 Pa)

<p>1 Type of installation: built-in 0/90/180/270°. Minimal distances authorised.</p> 	<p>2 Type of installation: remote from the wall, 0/180°. Minimal distances authorised.</p> 	<p>3 Type of installation: built-in 0/90/180/270°</p> 	<p>4 Type of installation: built-in 0/180°</p> 
--	---	---	--

Essential characteristics	Performance
Nominal activation conditions/sensitivity:	Pass
Response delay (response time): closure time	Pass
Operational reliability: cycling	MFUSP - 50 cycles; MMAG - 300 cycles; B(L)F(T); BFL(T); ONE; UNIQ - 10000 cycles
Durability of response delay:	Pass
Durability of operational reliability:	Pass
Protection against corrosion according to EN 60068-2-52:	Pass
Damper casing leakage according to EN 1751:	≥ class C

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:  
**Frank Verlinden**, Product Manager

*Frank Verlinden*  
 Oosterzele, 05/2018



Harmonised standard  
EN 15650:2010